

# Nitri-Solve®







**100% NITRILE GLOVE**  
**CHEMICAL-RESISTANT GLOVE**  
**NFPA 1992 COMPLIANT HAZMAT GLOVE**  
**FLOCK-LINED OR UNLINED**



## Chemical Resistant Glove:

### Characteristics:


| Style | Lining      | Sizes Available        | Thickness        | Length      |
|-------|-------------|------------------------|------------------|-------------|
| 717   | Unlined     | 06, 07, 08, 09, 10, 11 | 0.28 mm, 11 mils | 13" (330mm) |
| 727   | Unlined     | 06, 07, 08, 09, 10, 11 | 0.38 mm, 15 mils | 13" (330mm) |
| 730   | Flock-Lined | 06, 07, 08, 09, 10, 11 | 0.38 mm, 15 mils | 13" (330mm) |
| 737   | Unlined     | 08, 09, 10, 11         | 0.56 mm, 22 mils | 15" (330mm) |
| 747   | Unlined     | 07, 08, 09, 10, 11     | 0.56 mm, 22 mils | 19" (330mm) |

**Cat. III**    

#717 EN 388 #727/730 EN 388 #737/747 EN 388

**Performance Levels:**  
 Abrasion: Level 0-4  
 Cut Resistance: Level 0-5  
 Tear: Level 0-4  
 Puncture: Level 0-4

0123 2101 1101 3101

EN-374-3 2003 

Styles # 717/727/730  
 J (Heptane) 0 1 2 3 4 5 6  
 K (Sodium Hydroxide 40%) 0 1 2 3 4 5 6  
 L (Sulfuric Acid 96%) 0 1 2 3 4 5 6

Styles # 737/747  
 -(Cyclohexane) 0 1 2 3 4 5 6  
 K (Sodium Hydroxide 40%) 0 1 2 3 4 5 6  
 -(Hydrochloric Acid 37%) 0 1 2 3 4 5 6

J K L

### ANSI/ISEA 105-2005 Performance

|                 |                       |                 |
|-----------------|-----------------------|-----------------|
| <b>Abrasion</b> | <b>Cut Resistance</b> | <b>Puncture</b> |
| 0 1 2 3 4 5 6   | 0 1 2 3 4 5           | 0 1 2 3 4 5     |

### Description

Made from our special nitrile (NBR) compound, Nitri-Solve® provides excellent protection against abrasion, puncture, and snag and resistance to a broad range of solvents, animal fats and other chemicals. Permeation testing shows Nitri-Solve's chemical resistance is equal to or better than that of any other similar nitrile glove. Nitri-Solve's case-hardened finish enhances chemical and abrasion resistance and makes it easy to pull on and off. A bisque finish grip makes wet work easier, safer, and Nitri-Solve's ergonomic design maximizes comfort. Nitri-Solve is available in flock-lined and unlined styles in varying thicknesses and lengths for a wide range of applications. Each hand is embossed with glove size for ease of pairing after laundering.

### Suggested Applications

- Manufacturing
- Food Processing
- Hazmat Splash Protection
- Laboratories
- Janitorial
- Paint Applications
- Fuel Handling and Refineries

This list of suggested applications is partial and based on laboratory testing of glove performance. For a complete list of suggested applications, visit our website:

[www.showabestglove.com](http://www.showabestglove.com)

**USA:**  
 Showa Best Glove  
 579 Edison Street  
 Menlo, GA 30731  
 Phone: 800-241-0323  
 Fax: 888-393-2666  
 Email: [USA@showabestglove.com](mailto:USA@showabestglove.com)

**Canada:**  
 Showa Best Glove Manufacturing Ltd.  
 253 Michaud Street  
 Coaticook, Quebec J1A 1A9 Canada  
 Phone: 800-565-BEST  
 Fax: 819-849-6120  
 Email: [Canada@showabestglove.com](mailto:Canada@showabestglove.com)

**Europe:**  
 Showa Best Glove  
 Tour Franklin  
 La Defense 8  
 92042 Paris La Defense Cedex France  
 Tel Direct +33 (0)1 55 62 1420  
 Fax: +33 (0)1 55 62 1429  
 Email: [Europe@showabestglove.com](mailto:Europe@showabestglove.com)

**Australasia:**  
 Best Manufacturing Australia Pty. Ltd.  
 PO Box 187, Bexley  
 NSW 2207 Australia  
 Phone: +61 (0)2 8509 5401  
 Fax: +61 (0)2 8509 5403  
 Email: [Australiansales@bestglove.com](mailto:Australiansales@bestglove.com)